

PALLET FORKS

RAIL PALLET FORKS

Adjustable ITA Class II forged tines.

45.5"
FRAME WIDTH

UP TO
6200 LB
CAPACITY
(VARIES BY MODEL)

42" TO 60"
TINE LENGTHS

- 3/4" BEVELED RAIL
- BRICKGUARD FLUSH WITH TINES TO HELP STABILIZE LOADS
- BRACING CENTERED ON QUICK TACH FOR EASY HOOKUP
- BOLT-ON STEP INSTALLS ON EITHER SIDE

RAIL PALLET FORK - HI-VIS



- REMOVE CENTER SECTION TO CHANGE TO A WALK-THROUGH BRICKGUARD
- 1/4" HIGH VISIBILITY BRICKGUARD

RAIL PALLET FORK - WALK-THROUGH



- WALK-THROUGH DESIGN ALLOWS QUICK CAB ACCESS
- 1/4" HIGH VISIBILITY BRICKGUARD

RAIL PALLET FORK - HEX-GUARD



- 3/16" CLASSIC VIRNIG BRICKGUARD

MODEL	4240	4840	4255	4855	6055	4862
Width: Overall w/Step / Frame (in.)			50.5 / 45.5			
Overall Height (in.)	37.0					
Tine: Length / Width / Thickness (in.)	42.0/4.0/1.375	48.0/4.0/1.375	42.0/4.0/1.5	48.0/4.0/1.5	60.0/4.0/1.5	48.0/4.0/1.75
Tine Space: Min / Max (in.)	8.8 / 40.9					
Approximate Weight (lbs)	370*	390*	390*	405*	440*	420*
Capacity (lbs)	4000	4000	5500	5500	5500	6200

*PF model weights listed. Subtract 15 lbs for PFWT model weights. Subtract 25 lbs for PFHG model weights.