

STUMP BUCKET

Remove stumps, roots, and rocks.



1. COMPACT DEPTH MAXIMIZES LOADER BREAKOUT FORCE FOR REMOVING STUMPS
2. 3/4" x 6" WELD-ON EDGE WITH REPLACEABLE SERIES 23 TEETH (REPLACEMENT TEETH, PIN, & SHANK AVAILABLE)
3. BUCKET REINFORCED WITH LARGE GUSSET PLATES



MODEL	STMP
Overall Width (in.)	45.6
Height: Overall / Bucket (in.)	39.0 / 20.7
Overall Depth (in.)	46.3
Shovel Width: Bottom / Top (in.)	16.0 / 23.8
Space Between Teeth (in.)	3.3
Shovel Depth (in.)	29.6
Shovel Depth, With Teeth (in.)	37.3
Approximate Weight (lbs)	375
Recommended Loader Capacity	Greater than 1500 lbs

STUMP BUCKET GRAPPLE

Remove and transport stumps, roots, and rocks.



39.0" JAW OPENING	1-CYL SINGLE JAW GRAPPLE	STANDARD WITH CYLINDER GUARD
--------------------------------	---------------------------------------	--

1. COMPACT DEPTH MAXIMIZES LOADER BREAKOUT FORCE TO REMOVE STUMPS
2. 3/4" x 6" WELD-ON EDGE WITH REPLACEABLE SERIES 23 TEETH (REPLACEMENT TEETH, PIN, & SHANK AVAILABLE)
3. BUCKET REINFORCED WITH LARGE GUSSET PLATES
4. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGE

MODEL	STMPG
Overall Width (in.)	45.6
Height: Overall / Bucket (in.)	39.0 / 20.7
Overall Depth (in.)	46.3
Shovel Width: Bottom / Top (in.)	16.0 / 23.8
Space Between Teeth (in.)	3.3
Shovel Depth (in.)	29.6
Shovel Depth, With Teeth (in.)	37.3
Grapple Jaw Opening (in.)	39.0
Cylinder Bore / Stroke (in.)	2.0 / 8.375
Cylinder Pins / Hinge Pins Dia (in.)	1.25 / 1.563
Approximate Weight (lbs)	590
Recommended Loader Capacity	Greater than 1500 lbs