

V50 ROOT RAKE GRAPPLE

Available widths 66", 72" & 78"

High strength steel jaw and tines designed to dig, rake, pile, and load brush.



Known clearance issue with 66" URG on Takeuchi® TL6, TL8, TL10, TL12 and 72" URG on TL12. Also, 66" and 72" URG on John Deere® 330G, 331G, 332G, 333G have a clearance issue. No issues on other width URGs.

0.375" GRADE 80
STEEL TINES

44.0"
JAW
OPENING

22.1"
OVERALL
DEPTH

2-CYL
SINGLE-JAW
GRAPPLE

LESS THAN
2400 LB
LOADER OPERATING CAPACITY

1. NITROSTEEL® CYLINDER
RODS & TEFLON® COATED
BUSHINGS ON ALL PIVOTS

2. SERIES 23 PIN-ON TEETH
CUT INTO SOIL, DIG OUT
ROCKS & ROOTS
(REPLACEMENT AVAILABLE)

3. STANDARD WITH
CYLINDER GUARDS



MODEL	URG66	URG72	URG78
Overall Width (in.)	67.9	73.9	79.9
Height: Overall / Bucket (in.)		34.0 / 25.0	
Overall Depth (in.)		22.1	
Number of Teeth	6	7	8
Space Between Teeth (in.)	10.9	9.8	8.9
Space Between Tines, Grapple Jaws (in.)	8.8	11.1	10.1
Tine Thickness (in.)		0.375 ¹	
Cylinder Bore / Stroke (in.)		2.0 / 8.375	
Cylinder Pins / Hinge Pins Dia. (in.)		1.25 / 1.563	
Grapple Jaw Opening (in.)		44.0	
Approximate Weight (lbs)	790	845	905
Recommended Loader Capacity		Less than 2400 lbs	

¹Material is Grade 80 Plate (80,000 PSI Minimum Yield Strength).