

V50 SCRAP GRAPPLE

Available widths
60", 66", 72" & 78"

Solid bottom grapple for scooping and hauling loose and bulky debris.



AVAILABLE EDGE OPTIONS

See page 90 for additional information.



STANDARD BOLT-ON



SERRATED BOLT-ON

36.9" JAW OPENING	2-CYL INDEPENDENT GRAPPLE	< 2400 LB LOADER OPERATING CAP.
--------------------------	----------------------------------	---

1. 1/2" VERTICAL BRACES INSIDE BUCKET
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
3. 3/4" x 6" WELD-ON EDGE
4. STANDARD WITH CYLINDER GUARDS

	MODEL SBG60	SBG66	SBG72	SBG78
Overall Width (in.)	61.5	67.5	73.5	79.5
Height: Overall / Bucket (in.)	27.3 / 20.8			
Overall Depth (in.)	35.5			
Structural Wear Bars Under Bucket (1/2" x 4")	2	2	2	3
Cylinder Bore / Stroke (in.)	2.0 / 8.375			
Cylinder Pins / Hinge Pins Dia. (in.)	1.25 / 1.563			
Grapple Jaw Opening (in.)	36.9			
Approximate Weight (lbs)	895	930	965	1015
Recommended Loader Capacity	Less than 2400 lbs			

V60 SCRAP GRAPPLE

Available widths
72", 78", 84" & 90"

The toughest solid bottom grapple for scooping and hauling loose and bulky debris.



AVAILABLE EDGE OPTIONS

See page 90 for additional information.



STANDARD BOLT-ON



SERRATED BOLT-ON

38.8" JAW OPENING	2-CYL INDEPENDENT GRAPPLE	> 2400 LB LOADER OPERATING CAP.
--------------------------	----------------------------------	---

1. EXTRA BRACE PLATE & 1/2" VERTICAL BRACES INSIDE BUCKET FOR ADDED STRENGTH
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
3. 3/4" x 6" WELD-ON EDGE
4. STANDARD WITH CYLINDER GUARDS

	MODEL ISG72	ISG78	ISG84	ISG90
Overall Width (in.)	73.5	79.5	85.5	91.5
Height: Overall / Bucket (in.)	29.0 / 22.5			
Overall Depth (in.)	35.5			
Structural Wear Bars Under Bucket (1/2" x 4")	4	5	5	5
Cylinder Bore / Stroke (in.)	2.0 / 8.375			
Cylinder Pins / Hinge Pins Dia. (in.)	1.25 / 1.563			
Grapple Jaw Opening (in.)	38.8			
Approximate Weight (lbs)	1080	1130	1170	1210
Recommended Loader Capacity	Greater than 2400 lbs			