

Skid-Steer Loaders / S740 Skid-Steer Loader

S740 Loader Specifications & Options

■ Standard
☑ Optional
N/A Not Applicable

Units US

Bobcat S740

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	☒

Performance

Rated Operating Capacity (ISO)	3,100 lb
Tipping Load	6200 lb
Operating Weight	8794 lb
Travel Speed	7.1 mph
Travel Speed (2-speed option)	12.3 mph

Capacities

Fuel Tank	23.9 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/min
Auxiliary High Flow	30.5 gal/min

Dimension

Length	141.6 in
Length without Attachment	114.3 in
Length with Standard Bucket	141.6 in
Width	72.1 in
Width (with bucket)	74 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	131.4 in
Reach @ Maximum Height	33.6 in
Turning Radius	85.8 in
Wheelbase	48.3 in

Features

Joystick Control	☒
Air Conditioning	☒
Adjustable Seat	☐
Backup Alarm	☐
BICS System (Interlock)	☐
Cab Enclosure	☒
Sound Option	☒
Cab Heater	☒
Operating Lights	☐
Parking Brake	☐
Radio	☒
Rear Window	☐
Top Window	☐
Lift-Arm Support	☐
Seat Belt	☐
Suspension Seat	☐
Two Speed Travel	☒
Deluxe Instrumentation	☒
Engine Shutdown	☐
Hydraulic Bucket Positioning	☒
High Flow Option	☒
Auxiliary Hydraulics	☐
Spark Arrestor Muffler	☐
Bob-Tach Attachment System	☐
Power Bob-Tach	☒
ACS (Switchable Controls)	☒
Ride Control	☒
Rear Hydraulics	☒
Horn	☐

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.