

V20 MINI SKID STEER ANGLE BROOM

Available widths 48" & 60"

Direct drive Eaton® motor and exclusive self-centering swing linkage system for optimal sweeping.

CHOOSE FROM THREE MINI SKID MOUNTS:

- MINI UNIVERSAL (All brands except Bobcat® and ASV®)
- BOBCAT® Mini
- ASV® Mini

NOTE: None of the above are compatible with universal skid steer mount.



Standard with manual angle.
Standard with 26" diameter poly/wire wafers; all poly wafers also available.

10-18 GPM RECOMMENDED FLOW RATE	DIRECT DRIVE EATON® MOTOR	MANUAL & HYDRAULIC ANGLE AVAILABLE	GREATER THAN 500 LB LOADER OPERATING CAPACITY
---------------------------------------	------------------------------	--	---

1. SWING LINKAGE SYSTEM
SELF-CENTERS
BROOM WHEN ANGLED
2. RECESSED & GUARDED
MOTOR
3. HD 1.25" GREASEABLE
BEARING
4. REPLACE WAFERS
EASILY WITHOUT
DISCONNECTING HOSES.
STANDARD WITH POLY/
WIRE WAFERS.
5. STANDS FLIP DOWN TO
PROTECT BRISTLES
DURING STORAGE



OPTION:
HYDRAULIC
ANGLE
Angle the broom
from the loader.

MODEL	CAB48	CAB60
Sweeping Width, Straight (in.)	48.0	60.0
Sweeping Width, Full Angle (in.)	42.8	53.5
Loader Track Width Coverage, Full Angle (in.)	38.0	48.0
Overall Width (in.)	54.3	66.3
Overall Width, Full Angle (in.)	58.5	68.5
Overall Height/Depth, Straight (in.)	27.7 / 56.9	
Max Broom Angle (degrees)	28	
Number of 26 Inch Diameter Wafers	23	29
Recommended Flow Rate (GPM)	10-18 Standard Flow Only	
Approximate Weight (lbs)	495 ¹	530 ¹
Recommended Loader Capacity	Greater than 500 lbs	

¹ASV® mount adds approximately 30 lbs and Bobcat® mount adds 25 lbs to model weight.