

V50 CLOSED FRONT ROTARY BRUSH CUTTER

Available Widths 60", 66", 72" & 78"

HD finish mower with updraft blades to lift and process material for a quality finish, while optional rear roller and casters help smooth operation and protect turf.



Char-Lynn



Do not operate rotary brush cutter without a shatterproof cab on loader.

4.0" CUT CAPACITY	60"-78" FOUR CUT WIDTHS	14-45 GPM FIVE MOTOR OPTIONS STANDARD & HIGH FLOW	3500, 4100, 4500 PSI MAX OPERATING PRESSURE	ROLLER & CASTER OPTIONS
-------------------------	-------------------------------	---	--	-------------------------------


DETAIL UNDER DECK




**OPTION:
REAR ROLLER**
Rides slightly below
the deck for continuous
ground contact,
adding stability while
compacting material
and leaving a lawn-like
finish.



**OPTION:
PRESSURE GAUGE**
Monitor hydraulic
operating pressure for
max productivity.



**OPTION:
SWIVEL CASTERS**
Carries the front of the
deck at a consistent height
instead of digging into
the ground.



1.

DIRECT DRIVE EATON® GEROLER & SAI® PISTON MOTOR OPTIONS WITH PRESSURE RELIEF, MOTOR & SPINDLE GUARDS PREVENT DOWNTIME
2.

HYDRAULIC BRAKING STOPS FLYWHEEL WITHIN 10 SECONDS, CHAIN CURTAIN HELPS CONTAIN FLYING DEBRIS & LIFT LIMIT CHAIN PROTECTS OPERATOR
3.

ROUND FLYWHEEL TO GLANCE OFF OBJECTS & ENSURE UNIFORM ENERGY DISTRIBUTION TO EXTEND DRIVETRAIN LIFE
4.

3 UPDRAFT MACHINE-SHARPENED BLADES WITH 60% LONGER EDGE THAN INDUSTRY STANDARD TO PROCESS MATERIAL FOR A SUPERIOR FINISH
5.

REPLACEABLE FRONT SKID SHOES DESIGNED TO CUT GROUND LEVEL & HELP GLIDE OVER ROUGH TERRAIN
6.

TAPERED REAR DECK RUNNERS REDUCE GROUND DISTURBANCE

MODEL	RBC60-C	RBC66-C	RBC72-C	RBC78-C
Cut Width (in.)	60.0	66.0	72.0	78.0
Overall Height / Width / Depth (in.)	22.5 / 66.0 / 82.1	22.5 / 72.0 / 88.1	22.5 / 78.0 / 94.1	22.5 / 84.0 / 100.1
Deck Height (in.)	8.5			
Minimum Cut Height (in.)	1.9			
Cutting Capacity, Diameter (in.)	4.0			
Deck Thickness, Top / Side (in.)	0.25			
Recommended Flow Rate (GPM)	14-25 Standard Flow / 25-35 High Flow / 35-45 High Pressure			
Max Operating Pressure (PSI)	3500 Standard Flow / 4100 High Flow / 4500 High Pressure			
Flywheel Weight (lbs)	180	215	220	225
Approximate Weight (lbs)	1330 ¹	1470 ¹	1580 ¹	1690 ¹
Recommended Operating Cap (50%)	Greater than 1500 pounds			

¹Standard flow weight. High flow models add approximately 40-80 lbs to model weight.